

# Cambridge FL3B Series



### FEATURES & OPTIONS

#### Latch Backset

Exterior: 2-3/4" UL deadlatch standard  
Interior: 2-3/4" UL plainlatch standard  
(other options available)

#### Faceplate

1" x 2-1/4" square corner standard  
(other options available)

#### Bolt

1/2" throw

#### Door Thickness

Fit 1-3/8" to 1-13/16" standard

#### Cylinder

6-pin SC "C" keyway solid brass cylinder standard

Also available in:

5-pin KW keyway

6-pin small format interchangeable core

#### Strike Plate

2-1/4" x 1-3/4" full lip round corner standard  
(other options available)

#### Handing

Reversible for right or left handed doors

### SPECIFICATIONS

**Lockset:** Lock or latchset shall be by **PAMEX** model # **FL3B Series**. All locks shall provide with 3 hour rated solid brass plain or deadlatch. Lock chassis shall have individual springs for lever return to prevent lever sag.

### FINISHES

(other finishes available upon request with lead-time)

- US32D – 625 – Satin Stainless Steel**
- US3 – 605 – Polished Brass**
- US5 – 609 – Antique Brass**
- US26D – 626 – Satin Chrome**

### CODE COMPLIANCE

- Meets ANSI/BHMA A156.2, **Series 4000, Grade 2**
- Meets ADA Requirements
- **UL 3-Hour Fire Rated**

### WARRANTY

- **Lifetime mechanical warranty**
- **Five years finish warranty**



### FUNCTIONS

#### Entry – F190 (FL30B/FL30C)

Outside lever locked or unlocked by key outside or **turn-piece (FL30B) / push-button (FL30C)** inside. Inside always free.

#### Privacy – F76 (FL31B/FL31C)

Outside lever locked or unlocked by **turn-piece (FL31B) / push-button (FL31C)** inside or by a coin or screwdriver outside. Inside always free.

#### Passage – F75 (FL33B)

Both levers always free.

#### Half Dummy (FL34B)

Single dummy trim for pull only.

#### Storeroom – F86 (FL35B)

Outside lever always fixed and unlocked by key only. Inside lever always free.

#### Classroom – F84 (FL38B)

Outside lever locked or unlocked by key. Inside lever always free.

