


GC4400 Series



FEATURES & OPTIONS

- UL Listed (UL 10C)
- Universal application and non-handed installation (regular and parallel bracket included)
- Multi-size strength, power adjustable for size 1 thru 6 (factory preset size 3)
- Heavy duty cast iron body w/ rust inhibiting treatment
- Hardened steel rack and pinion mechanism
- Needle bearings for higher efficiency smooth opening
- Adjustable back check standard
- Fixing for both metal and timber doors
- Adjustable closing and latching speed
- Optional delay action
- Door weight range from 33 ~ 176 lbs
- Stable hydraulic fluid capable of withstanding temperature ranges of 105 degrees F. to -25 degrees F.

PACKAGE INCLUDES

- Parallel bracket
- Wood screws and machine screws
- Full plastic cover
- Sex bolts and Thru bolts

FINISHES

- Aluminum (painted)
- Dark Brown (painted)

WARRANTY

- 25 years mechanical warranty
- Five years finish warranty



CODE COMPLIANCE

- ANSI A156.4 Grade 1
- UL10C and UBC 7.2 for positive pressure
- Meets ADA barrier-free accessibility

SPECIFICATIONS

Closer: Closers shall be by Pamex model # **GC4400**, full rack and pinion type with cast aluminum alloy body. All closers shall be provided with non-critical valves adjustment to independently regulate the sweep, latch and back-check. Closer shall have full spring adjustment from size 1 to 6 for barrier free (BF).

