

# EF4000

## Rim Type



### FEATURES & OPTIONS

**Fire Rated Rim Type Exit Device**

**Door Width**

For all doors up to 36" or 48" wide

**Stile**

4-1/4" minimum

**Material**

Push bar is made of extruded anodize aluminum and spring is made of stainless steel

**Strike**

For 5/8" stop, plus shim for 1/2" stop

**Latch Bolts**

3/4" throw, stainless steel

**Dead Latch Bolts**

5/8" stainless steel

**Mounting**

Furnished standard with sheet metal & machine screws and SNB

**Backset**

2-3/4" standard

**Handing**

Non-handed

**Projection**

2-1/2" maximum projection, 1-7/8" when depressed

**Operation**

Exit by slight pressure on any point on the push bar at all time

### SPECIFICATIONS

**Exit Device:** Exit device shall be by **Pamex** model # **EF4000** for UL fire barrier doors. All exit devices shall be modern push pad type, non-handed and provided with thru bolts for proper installation. EF4000 is UL listed for 3 hour fire and egress. Exit device shall be narrow profile; projecting only 2-1/4" from the surface of the door.

### FINISHES

- Aluminum (Painted)
- Dark Bronze (Painted)
- Stainless Steel

### WARRANTY

- Ten years mechanical warranty
- Five years finish warranty



### CODE COMPLIANCE



- ANSI A156.3, Grade 1
- UL listed for Panic and UL10C, UBC 7-2-1997 codes
- UL 1-1/2 Hour Fire Rated

### Available Trims



Heavy Duty  
Lever Trim  
(Handed)



Lever Trim



Knob Trim



Rim Cylinder  
Single Pull



Rim Cylinder  
Double Pull



Cover Plate



Pull Plate

