

# Springfield

## FSC Series

### FEATURES & OPTIONS

#### Door Prep.

Cross Bore: 2-1/8", Edge: 1"  
Center to Center: 5"

#### Interior Trim

FT3-Saturn knob interior trim  
(other options available)

#### Latch Backset

Deadbolt: 2-3/8" deadbolt standard  
Handle: 2-3/8" plainlatch standard  
(other options available)

#### Faceplate

1" x 2-1/4" round corner standard  
(other options available)

#### Bolt

Deadbolt: 1" throw  
Lever: 1/2" throw

#### Door Thickness

Fit 1-3/8" to 1-3/4" standard  
(extension kit available for 1-3/4" to 2-1/4" door)

#### Cylinder

5-pin KW keyway solid brass cylinder standard  
5-pin SC "C" keyway available

#### Strike Plate

Deadbolt: 2-1/4" x 1-3/4" full lip round corner standard  
Handle: 2-1/4" x 1-3/4" full lip round corner standard  
(other options available)

#### Handing

Specify handing when order lever interior trim

#### ANSI/BHMA

A 156.2 Grade 3

### FINISHES

(other finishes available upon request with lead-time)

- US3 – 605 – Polished Brass
- US5 – 609 – Antique Brass
- US15 – 619 – Satin Nickel

### WARRANTY

- Lifetime mechanical warranty
- Five years finish warranty

### FUNCTIONS

#### Single Cylinder (FSC1)

Deadbolt operated by key outside and turn-piece inside. Latchbolt operated by thumb-piece outside and knob or lever inside.

#### Double Cylinder (FSC2)

Deadbolt operated by key on both sides. Latchbolt operated by thumb-piece outside and knob or lever inside.

#### Dummy (FSC4)

Handle and knob or lever act as pull only. No operation.

